


塑料防水电缆接头 M 型 Plastic waterproof cable connector M type



产品材质：采用 UL 认可的尼龙 PA66  
 密封件：丁晴橡胶 (NBR)，耐候橡胶 (EPDM)  
 工作温度：静态 -40°C 至 100°C，瞬时耐热至 120°C，动态 -20°C 至 80°C，瞬间耐热至 100°C  
 防护等级：IP68( 旋紧部位，并使用 O- 密封圈 )  
 颜色种类：黑色 (RAL9005)、浅灰 (RAL7035)，特殊颜色可定做

Product material: Nylon PA66 approved by UL  
 Sealing parts: Butadiene rubber (NBR), weatherproof rubber (EPDM)  
 Operating temperature: static -40°C to 100°C, instantaneous heat resistance to 120°C, dynamic -20°C to 80°C, instant heat resistance to 100°C  
 Protection level: IP68 (tighten the part and use O-seal ring)  
 Color type: black (RAL9005), light gray (RAL7035), special color can be customized

产品型号 Model	适用电缆 Cable Range(mm)	螺纹外径 Thread O.D. AG (mm)	螺纹长度 Thread Length GL(mm)	扳手直径 Spanner Size(mm)
PG7	3~6.5	12.5	8	16
PG7	2~5	12.5	8	16
PG9	4~8	15.2	8	19
PG9	2~6	15.2	8	19
PG11	5~10	18.6	8	22
PG11	3~7	18.6	8	22
PG13.5	6~12	20.4	10	24
PG13.5	5~9	20.4	10	24
PG16	10~14	22.5	10	27
PG16	7~12	22.5	10	27
PG19	12~16	24	10	27
PG19	10~13	24	10	27
PG21	13~18	28.3	10	33
PG21	9~16	28.3	10	33
PG25	16~21	30	11	35
PG25	13~18	30	11	35
PG29	18~25	37	12	42
PG29	13~20	37	12	42
PG36	22~32	47	14	52
PG36	20~26	47	14	52
PG42	32~38	54	14	60
PG42	25~31	54	14	60
PG48	37~44	59.3	15	64
PG48	29~35	59.3	15	64
PG63	42~50	71	28	77
PG63	32~40	71	28	77

产品型号 Model	适用电缆 Cable Range(mm)	螺纹外径 Thread O.D.AG (mm)	螺纹长度 Thread Length GL(mm)	扳手直径 Spanner Size(mm)
M12×1.5	3~6.5	12	8	16
M12×1.5	2~5	12	8	16
M16×1.5	4~8	16	8	19
M16×1.5	2~6	16	8	19
M18×1.5	5~10	18	8	22
M18×1.5	3~7	18	8	22
M20×1.5	6~12	20	10	24
M20×1.5	5~9	20	10	24
M22×1.5	10~14	22	10	27
M22×1.5	7~12	22	10	27
M24×1.5	12~16	24	10	27
M24×1.5	10~13	24	10	27
M25×1.5	13~18	25	10	33
M25×1.5	9~16	25	10	33
M27×1.5	13~18	27	10	33
M27×1.5	9~16	27	10	33
M30×1.5	16~21	30	11	35
M30×1.5	13~18	30	11	35
M32×1.5	16~21	32	11	35
M32×1.5	13~18	32	11	35
M36×1.5	18~25	36	12	42
M36×1.5	13~20	36	12	42
M40×1.5	22~32	40	14	52
M40×1.5	20~26	40	14	52
M50×1.5	32~38	50	14	60
M50×1.5	25~31	50	14	60
M63×1.5	37~44	63	15	64
M63×1.5	29~35	63	15	64
M71×1.5	42~50	71	28	77
M71×1.5	32~40	71	28	77